

Poly Trio C60 IP Conference Phone and PoE-enabled No Radio

One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.



*Product image may differ from actual product

Poly signature audio

Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.

One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

[Datasheet](#)

Poly Trio C60 IP Conference Phone and PoE-enabled No Radio

Specifications



Display

Aspect ratio: 16:9
 Native resolution: 720 x 1280
 Panel technology: Color LCD
 Display size (diagonal): 5'
 Display size (diagonal, metric): 12.7 cm (5")
 Touch-enabled: Gesture-based, multi-touch capable touchscreen

Connectivity and communications

Wireless range: Up to 61 m
 Wireless range (imperial): Up to 20 ft
 External I/O ports:
 1USB 2.0 Type-A (for USB battery charging)
 1USB 2.0 Micro-B (for USB audio device)
 2RJ-45 (10/100/1000BASE-TX Mbps)

Battery

Power features:
 LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)
 LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment¹

User interface features

Languages:
 Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:
 Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
 Comfort noise generation
 DTMF-tone generation (RFC 2833 and in-band)
 Low delay audio packet transmission
 Adaptive jitter buffers
 Microphone type: Three cardioid microphones
 Frequency response (microphone): 100 Hz to 22 kHz
 Sensitivity (speaker): 92 dB
 Audio codecs:
 G.711(A-law and μ-law)
 G.722
 G.7221C
 G.729AB
 G.719
 Polycom® Siren™ 7
 Siren™ 14
 iLBC
 OPUS

Environmental

Certifications and compliances: AS/NZS 60950-1; AS/NZS 62368-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-114; CE Mark; CISPR22 Class B; EN 301 489-1; EN 301 489-3; EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9; ETSI EN 300 330; ETSI EN 301 893 v1.7; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / 32 to 104°F

Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -20 to 70 °C / -40 to 158°F

Energy star certified: ENERGY STAR® certified

Certifications

Certified collaboration software: Microsoft Teams; Skype for Business; Zoom

Special features:
 Unicode UTF-8 character support

Applications supported

Management software:
 Poly Zero Touch Provisioning
 RealPresence Resource Manager (v. 10.1 or above) based provisioning
 Polycom Device Management Service for Enterprise (PDMS-E)
 Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management
 SDP

Display features

On-screen virtual keyboard

Security

Security management:
 802.1X Authentication and EAPOL. Media encryption via SRTP
 Digest authentication
 Encrypted configuration files
 HTTPS secure provisioning
 Password login
 Support for signed software executables
 Support for URL syntax with password
 Transport Layer Security (TLS)
 Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)
 FIPS 140-2 compliant cryptographic module

Network

Supported network protocols:
 DHCP VLAN discovery
 LLDP-MED for VLAN discovery
 FTP/TFTP/HTTP/HTTPS server-based central provisioning
 Manual or dynamic host configuration protocol (DHCP) network setup
 QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
 Time and date synchronization using SNTP
 Provisioning and call server redundancy support
 VoIP features:
 IETF SIP (RFC 3261 and companion RFCs)

Poly Trio C60 IP Conference Phone and PoE-enabled No Radio

Specifications



Telephony and call handling features:

Bundled with Polycom UC Software: Corporate Directory Access using LDAP
 Call timer and call waiting
 Call transfer, hold, divert (forward), park, pickup
 Called, calling, connected party information
 Distinctive incoming call treatment/call waiting
 Do not disturb function
 Local configurable digit map/dial plan
 Local five-way audio conferencing
 Shared call/bridged line appearance
 Visual Conference Management
 Up to 3 lines (maximum one Skype for Business and Microsoft Teams)
 Daisy-chain up to four
 One-touch speed dial, redial and meeting join

Weight and dimensions

Product Primary Color: Black
 Weight (Imperial): 21 lb
 Weight (Metric): 950 g
 Product dimensions (Imperial): 15.1 x 2.9 x 13.1 in
 Product Dimensions (Metric): 38.3 x 75 x 33.2 cm
 Package dimensions (Imperial): 19 x 4.5 x 15.5 in
 Package dimensions (Metric): 48.3 x 11.5 x 39.4 cm
 Package weight (Imperial): 4.3 lb
 Package Weight (Metric): 1970 g
 Product number: 830A2AA

Warranty

Poly standard one-year limited warranty

What is in the box

Console
 Network (LAN) cable-CAT-5E
 USB Type-A cable
 Cable wrap
 Tactile overlay for improved accessibility
 Setup sheet

Technical Specifications Footnotes

¹Requires full Class 4 power input on LAN IN for operation

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. July 2023